

# ProSafe Isolation Transformers

- ▶ Fully Isolates Boats AC System from Shore Power AC
- ▶ Eliminates Galvanic Current Flow & Corrosion
- ▶ Eliminates the Need for an ABYC Compliant Monitored Galvanic Isolator
- ▶ Ultra Quiet Operation
- ▶ Low Idle / Stand-by Current
- ▶ Eliminates "Neutral Drop Out" on 120 / 240 Volt Installations
- ▶ 6 User Selectable Cable Thru Hole Locations - Maximum Installation Flexibility
- ▶ Easy Access Terminal Block Connections on All Models
- ▶ Strain Relief Kit Included with Each Model
- ▶ Fully Encapsulated - Shock & Vibration Resistant Design
- ▶ 1 Year Limited Warranty
- ▶ Made in the USA



Ultra Quiet Operation

## 4 Models to choose from:



3.6 KVA - 120 VAC 60 Hz

Listed to: cUL, UL506, ABYC E-11

3.8 KVA - 120/240 VAC 50/60 Hz

Listed to: CE, cUL, UL506, ABYC E-11

12.0 KVA- 240 VAC 60 Hz

Listed to: cUL, UL1561, ABYC E-11

12.0 KVA- 120/240 VAC 50/60 Hz

Listed to: CE, cUL, UL1561, ABYC E-11

## Specifications

model	description	UL part no.	kilovolt amps	input current	input/output voltage	frequency	output current	size (d x w x h)	weight
21036	ProSafe Isolation Transformer 3.6 KVA	411-SA02-036	3.6 KVA	30 amps	120 VAC	60 Hz	30 amps	6.75" x 7.5" x 9.63"	65 lbs.
21038	ProSafe Isolation Transformer 3.8 KVA	411-SU02-038	3.8 KVA	32/16 amps	120/240 VAC	50/60 Hz	32/16 amps	6.75" x 7.5" x 9.63"	70 lbs.
21040	ProSafe Isolation Transformer 12.0 KVA 60 Hz	411-SA02-120	12.0 KVA	50 amps	120/240 VAC*	60 Hz	25/50 amps	8.5" x 13.5" x 16"	175 lbs.
21042	ProSafe Isolation Transformer 12.0 KVA 50/60 Hz	411-SU02-120	12.0 KVA	50 amps	120/240 VAC*	50/60 Hz	25/50 amps	8.5" x 13.5" x 16"	175 lbs.

\*12 KVA transformer is 220 Volt center tapped